

# TEKNOFLOR®

HIGH PERFORMANCE FLOORING



NO WAX  
NO BUFF  
EASY TO  
CLEAN

MOUNTAINSCAPES™  
COMMERCIAL RESILIENT SHEET FLOORING

# VINTAGE LINOLEUM MADE IRRESISTIBLE.

**TEKNOFLOR® Mountainscapes™ Collection.** Our **Mountainscapes** collection features attractive aspects of nature in a classic linoleum look. The result is a beautiful floor that pays homage to its retro inspiration while fully embracing the advanced **TEKNOFLOR** technology that propels it into the modern era. An advanced flooring system that is as unique as it is durable and functional. For more information, contact your Teknoflor sales representative.



## ULTRA-REALISTIC

- Digital imaging and high resolution offset printing process

## DURABLE AND LOW MAINTENANCE

- **No Wax, No Buff;** Easily cleaned by damp mopping or auto-scrubbing
- Difficult to scuff or scratch
- Thicker, 2.3mm gauge for enhanced performance in heavy traffic areas
- Maintenance savings result in investment payback in approximately two years

## ENVIRONMENTALLY FRIENDLY

- Antimicrobial agent incorporated into the wear layer which effectively inhibits bacterial growth on the flooring surface
- No buff floors mean no bacteria, dust or wax particles are thrown into the air during cleaning
- No odors from floor finishes or strippers; no wax flushed into sewer system
- Potentially 1-2 LEEDs points under LEED MR Credit 4.1-4.2

## SAFE

- ADA Compliant
- Meets fire test standards and is suitable for use in emergency exits and corridors

## OVERALL THICKNESS

- 2.3 mm (0.090")

## WARRANTY

- 12-year commercial warranty

## APPLICATIONS

- Ideal for Healthcare, Senior Living, Corporate/Office, Retail, Hospitality, Academic and Educational Environments

MOUNTAINSCAPES™

COMMERCIAL RESILIENT SHEET FLOORING

TEKNOFLOR®



88041 Buckskin



88032 Hacienda



88043 Mesa



88030 Sand



88035 Flaxen



88042 Chaparral




88001 River



88009 Canyon



88034 Citrine



88008 Trail




88040 Palisades



88021 Oyster



88002 Mist



88003 Moss

# TEKNOFLOR® MOUNTAINSCAPES™

COMMERCIAL RESILIENT SHEET FLOORING

PRODUCT DATA	
STANDARD SPECIFICATION	ASTM F1303
CLASSIFICATION	Type I Grade 1
BACKING CLASS	Class A 4-Ply fused backing system comprised of PVC Layer, Fiberglass, PVC Internal layer and PVC backing layer
DIMENSIONS	6' Wide x 75' Long
ROLL SIZE	50 Square Yards (275 lbs. per roll)
WEIGHT	5.5 lbs. per Square Yard
OVERALL THICKNESS	2.3 mm (0.090")
WEAR LAYER THICKNESS	20 mils
PATTERN REPEAT	72"w x 39.3"L (No Pattern Match is required)
WARRANTY	12-Year

SAFETY & PERFORMANCE	TEST METHOD	STANDARD REQUIREMENT	RESULT
CHEMICAL RESISTANCE	ASTM F925	0- No change or 1 - Slight Change	Exceeds requirements
HEAT STABILITY COLOR CHANGE	ASTM F1514	$\Delta E < 8.0$ avg. @7 days	Passes
LIGHT STABILITY COLOR CHANGE	ASTM F1515	$\Delta E < 8.0$ avg. @300 hrs.	Passes
STATIC LOAD LIMIT	ASTM F970	250 psi $\leq$ 0.005" Residual Indentation	Exceeds Requirements 1,000 psi at maximum limit
FLOORSCORE	Certified		Certification # SCS-FS-04567
ABRASION RESISTANCE	ASTM D4060	H18 Wheel & 1 kg mass applied	19,000 Cycles until design layer visibly affected
STATIC COEFFICIENT OF FRICTION (SCOF)	D2047	$\geq 0.5$ SCOF Dry	$\geq 0.6$ SCOF Dry
CRITICAL RADIANT FLUX	E648	Class I: $\geq 0.45$ w/cm <sup>2</sup> Class II: $\geq 0.22$ w/cm <sup>2</sup>	Class I
SMOKE GENERATION	E662	<450 Flaming & Non-Flaming	<450 Flaming & Non-Flaming
<b>APPROVED FOR EMERGENCY EGRESS AREAS - NFPA 101</b>			



Schedule  
GS-27F-0504H • GS-27F-0036V  
GS-27F-0015V

