

Declare. SM

TEKNOFLOR™ Bio-Polyurethane Flooring Teknoflor

Final Assembly: Detmold, North Rhine-Westphalia, Germany;
Augustdorf, North Rhine-Westphalia, Germany
Life Expectancy: Commercial - 12 Years, Residential - 20 Year(s)
Embodied Carbon: 4.26 kg CO₂-eq
Declared Unit: 1 square meter of resilient flooring
End of Life Options: Take Back Program (Continental U.S.)

Ingredients:

Fillers: Calcium carbonate; Zeolite; **Polymer:** Polyurethane;
Nonwoven: Glass; Polyester; Polypropylene; **Flame Retardant:**
Aluminium hydroxide; **Décor Paper:** Cellulose; **Décor Paper
Filler:** Kaolin; **Décor Paper Pigment:** Titanium dioxide;
Additives and Décor Paper Dyes: Undisclosed (0.5-1%)¹; **Foam
Regulator:** White Oil

¹LBC Temp Exception RL-004b - Proprietary Ingredients in
Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 99% at 100ppm
 LBC Red List Approved VOC Content: Not Applicable
 Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

TEK-0003
EXP. 01 MAY 2022
Original Issue Date: 2018

