





5705 GRAPHITE



5757 LAVENDER




5701 PEARL




5744 ALLURE



5713 GRANITE



5726 CANARY



5753 AQUAMARINE




5731 BERRY




5721 MOON ROCK



5754 SERENITY



5775 MYSTIC




5714 ICE GREY




5711 SILVER GREY



5755 OZONE




5765 SEA FOAM




5762 THORN APPLE



5727 HUMMUS




5723 MOROCCO




5728 MAYAN MAIZE




5722 DUSTY



5766 JADE



5773 MESA




5743 TERRACOTTA




5702 CAPE COD



5725 SHELL




5746 RUST




5712 CONCRETE



5768 PINE




5761 APPLE MINT



5767 VERDE




5763 SPRUCE




5724 CORUNDUM




5772 MOJAVE SAND




5715 METEORITE



5704 STONE GREY



5741 ROSE BEIGE




5703 PEWTER




5732 CAROTENE




5774 ASPHALT



5742 MEXICALI ROSE




5751 BLUE MIST




5752 BLUE MOON



5706 MIDNIGHT



5759 DENIM



5756 LILAC




5745 MARS




5729 SUNBEAM




5764 AMBROSIA



5776 CURRY



5758 BLUE ORCHID



5716 STORMY

Philip J. Hughes
Fed Gov - DoD
GSA Account Manager

937-829-8316
phughes@teknoflor.com
www.vip.vetbiz.gov

SDVOSB GSA Schedule
GS-27F-0036V VAMC VIP Verified CAGE
Code: 4RRA8

PRODUCT	Zero	EN 14565	PVC- and plasticizer-free Enomer® flooring	
	Application	EN ISO 10874	23 / 34 / 43	
SPECIFICATION	Thickness	EN ISO 24346	~0.08" (2.0 mm)	
	Weight	EN ISO 23997	~0.64 lbs / sq ft (3100 g/m²)	
	Roll length	EN ISO 24341	82.02' (10 - 25 m)	
	Width	EN ISO 24341	4'9" (145 cm)	
PRODUCT PROPERTIES	PROPERTY	TEST METHOD	RESULT	
	Indoor Air Certifications		Blauer Engel, M1, FloorScore, Austrian Ecolabel	
	Electrostatic Propensity	AATCC 134	< 2.0 kV	
	Electrical Resistance	ASTM F 150	> 50 GΩ	
	Slip Resistance DCOF (Wet)	ANSI B 101.3	Acceptable	
	Static Coefficient of Friction	ASTM C 1028	Pass	
	Abrasion Resistance w weight loss	ASTM D 4060	< 0.05 g / 1000 cycles	
	Castor Chair Test 25.000 cycles	EN 425	Pass	
	Critical Radiant Flux	ASTM E 648	≥ 0.45 W/cm² Class 1	
	Smoke Density	ASTM E 662	≤ 450 Flaming & Non-flaming	
	Flexibility	ASTM F 137	Pass (8 mm mandrel)	
	Resistance to Heat	ASTM F 1514	Pass	
	Resistance to Light	ASTM F 1515	Pass	
	Short Term Indentation	ASTM F 1914	0.003" at 75 lbs	
	Chemical Resistance	ASTM F 925	Excellence	
	Static Load Limit	ASTM F 970	0.001"	
Static Load Limit	ASTM F 970 Mod	2000 psi		
Improvement in Impact Insulation Class (ΔIIC)	ASTM E 2179-09	9		

Cleaning and maintenance instructions, see: www.upofloor.com



www.blauer-engel.de/uz120